

HS102 Network security application platform

Intel®LGA1151 6th/7th core, Six-Port RJ45 & Quad-Port SFP, Expansion 2 slots

Overview



HS102 is a independently developed multi port intelligent gateway by Shenzhen Lianrui Electronics Co., LTD based on ® LGA1151 6th/7th Celeron/Primum/Corei3/i5/i7 series processor, which is widely used in industrial automation, communication, transportation, education, medical and other industries.

Point:

- 1. Support LGA1151 socket 6th/7th gen Inter Core®i7/i5/i3,Pentium &Celeron®or Xeon E3-1200 V5 Processor
- 2. 2U 19 "rack mounted network security application platform
- 3. Supports 4 * DDR4 2133MHz DIMM memory, with a maximum of 64GB
- 4. Modular design, It Support 2 PCle expansion slots, expandable 10G Quad-port RJ45/Quad-portSFP/Eight-port RJ45/Eight-port SFP
- 5. Support 6 * 1G RJ45 network card, 4 * 1G SFP network card
- 6. It support 4 * SATA3.0 interface. 1 * CF expansion card
- 7. Compatible with 1U single power supply

Sales: service@lr-link.com
Support: support@lr-link.com

Product model	HS102					
Controller	Support LGA1151 socket 6th/7th gen Intel® Corei7/i5/i3, Pentium &Celeron®or Xeon E3-1200					
Controller	V5 Processor					
Chipset	Intel "C236 Chipset					
Memory	supports 4 * DDR4 2133MHz DIMM memory, with a maximum of 64GB					
Bus Type	2 *PCIEx8					
LAN	The network chip is an I211AT 1G network card, and the SFP is a 12101S 1G network card.					
LAN	LAN3\LAN4. LAN5\LAN6 supports the bypass function					
	4*1G SFP					
	2*USB 2.0					
Front panel IO	6*1G RJ45					
	1xCOM					
	PWR LED/HDD LED					
Rear panel	1*Power Switch					
iteal pallel	1*AC Jack					
Power Supply	Supply 250W power					
01	2xSATA3.0 2.5"&3.5"					
Storage	1xCF connector					
Size	430mm(W)x550mm(D)x44.5mm (H)					
Weight	Net weight 8Kg					
Operating	0°C~50°C					
Temperature	0 0 0 0					
Storage Temperature	-20℃~75℃					
Storage Humidity	5%~95% (Non condensing)					

For more product information, please refer to http://www.lr-link.com

No.	Model	Processor	Memory	VGA	CONSOLE	USB	Interface	Scalable	Power
1	HS102	Support 6th/7th Celeron /Pentium/ Corei3/i5/i7 Series Processor	Support 64G (maximum)	1	1	2	Integrated 6*1G	2*PCIE	AC 220V

Ordering information

Remarks: The above information is for reference only, subject to change without notice.

Download Drivers

To get the drivers, please visit us at http://www.lr-link.com/support/driver.html.

Product Quick Guide

To know the network card basic knowledge to choose the suitable NIC you need, please visit us at: http://www.lrlink.com/productchoose.html.

Customer Support

LR-LINK customer Support Services offers a broad selection of programs including phone support and warranty service. For more information, contact us at Service and availability. http://www.lr-link.com/contactus.html

Shenzhen Lianrui Electronics Co.,LTD.

Shenzhen Lianrui Electronics Co.,Ltd is an efficient Ethernet adapter design company with independent research and development, using Intel, Net-swift, Tehuite, Broadcom, Realtek and other manufacturers Ethernet controller, developed by our company's independent R & D design team, manufactured by our company workshop, and then sell.

Declaration

Our products specifications come from modifying the chip manufacturer's specifications released. Product features, technical parameters, technology right, intellectual property rights and brand names etc. mentioned in specifications are just referenced only. There is no infringement meaning. If there is any important andsensitive content related, please contact our Lianrui company, we'll delete them, Thank you.

SHENZHEN LIANRUI ELECTRONICS CON.,LTD.

ADD:C4 Bldg., Xintang Industry Zone, Baishixia Fuyong Town, Baoan District Shenzhen China Tel:+86(0)755-33671531 33671533 Fax:+86(0)755-29082065

Product Sales: sales @lr-link.com Technical Support: support@lr-link.com

Web: www.lr-link.com



Copyright © Shenzhen Lianrui Electronics CO.,LTD,2006-2022. All rights reserved